



TSIRCON CO LTD

MANUFACTURERS & TRADERS
OF BUILDING MATERIALS

TSIRCO-POLYCRETE TA

Product: Cement base tile adhesive mortar with excellent bond strength.

Composition: One part cement base polymeric tile adhesive.

Powerful Bonding: Excellent adhesion to most building materials such as concrete, plaster, masonry block, brick, etc. It is also ideal for water retaining structures.

Introduction: Tsirco-Polycrete Tile adhesive is an economical and easy to use material.

Advantages:

- Mixes only with water
- Non- hazardous
- Non- flammable
- Low odour
- Highly water resistant
- Can be used for interior and exterior applications, for both floor and wall installations.
- High adhesion properties

Uses:

- On gypsum walls or gypsum based mortars
- On gypsum boards
- On walls or floors
- Over under floor heating
- Water retaining walls
- Cement plaster
- Concrete and concrete masonry
- Brick masonry
- Cement Tarrazzo



TSIRCON CO LTD

MANUFACTURERS & TRADERS
OF BUILDING MATERIALS

Packing: 10kg,20kg,40kg

Approximate coverage: 2-5kg/m²

Properties:

Colour: Grey when mix

Specific gravity: approx. 2,0kg/lit (when mixed)

Maximum particle size: 0.3mm

Pot life:1,5-2,0 hours at 20°C

INSTRUCTION FOR USE:

Surface preparation: All concrete must be clean, sound and free from oil, grease and cement laitance. Substrate shall be thoroughly prewetted before application. All metal surfaces must be free from corrosion.

Mixing: Add the 20kg ready for use product in approximately 6,6lit clean water and mix using mechanical slow speed stirrer until an even, smooth consistency has been reached. Leave the mix to stand for 3min and re-mix again.

Application: Immediately after, pour the grout ensuring that air can be displaced and that sufficient head of pressure is maintained to keep the mortar flowing.

Important Hints

*It is important that concrete surfaces are prewetted.

*At all times during the pouring of the grout, maintain a light rod movement to increase flow.